

AOA-5815

5.1~5.9GHz 15dBi Omni Antenna

AOA-5815 antennas are professionally engineered and manufactured with the highest industry quality at the lowest possible price providing extreme value.

AOA-5815 is designed for the 5.8GHz ISM band, supporting 5.1 to 5.9 GHz and provides superb performance in IEEE 802.11a WiFi applications.

AOA-5815 includes mounting bracket and hardware for up to 2" OD masts. Made with fiberglass

Applications:

5.1 – 5.9 GHz ISM Band
5.3 GHz Band Applications
5.4 GHz Band Applications
5.8GHz UNII applications
IEEE 802.11a Wireless LAN
Unlicensed European 5.4 GHz Band Applications
5.8 GHz Wireless Video Systems
WiMAX Technology

Features:

Superior performance
Light weight
All weather operation
DC Short lightning protection
Installed for vertical
Includes tilt and swivel mast mount
Frequency Ultra-wide
Can be installed for either vertical or horizontal polarization
RoHS Compliant



Model	AOA-5815
Frequency	5.1-5.9GHz
VSWR	≤ 1.5
Gain	15dBi
Polarization	Vertical
Power Handling	50 Watts
Impedance	50 Ω
Beam Width	H: 360° / V: 7°
Connector	N Female
Operation Temp	-40°C ~ +80°C
Dimension	740*68 mm
Mounting	32 ~ 45 mm (1.2 ~1.75 inch)
Weight	440g


For further details:

Alfa Network Inc.,
4F-1 No. 106, Rueiguang Rd.,
Neihu District,
Taipei City, Taiwan.
<http://www.alfa.com.tw>
sales@alfa.com.tw
Tel:+886-2-27968477
Fax:+886-2-27968478


AOA-5815

5.1~5.9GHz Omni Antenna 15dBi

Network Analyzer Test Report



Return loss




V.S.W.R


AOA-5815

5.1~5.9GHz Omni Antenna 15dBi

RF Chamber Test Report Frequency: 5.1 ~ 5.9GHz




Vertical Pattern Photos



Horizontal Pattern Photos


Frequency: 5.1-5.9Ghz

E-plane co-pol ----- 3-dB beam-with=7 Deg



Vertical Pattern

H-plane co-pol ----- 3-dB beam-with=360 Deg





Horizontal Pattern

AOA-5815

5.1~5.9GHz Omni Antenna 15dBi


Mounting Kits Install Guide



2:5



1.



2.



3.

Finish

